

SMART SMART6-L™



DUAL-FREQUENCY GNSS SMART ANTENNA FEATURING NOVATEL'S POWERFUL OEM6® TECHNOLOGY



SCALABLE PERFORMANCE

From single-frequency GLIDE™ autonomous tracking to dual-frequency Real Time Kinematic (RTK), the SMART6-L positions you for success. The SMART6-L integrates NovAtel's OEM6 receiver and Pinwheel® antenna technologies in a single, rugged housing. Software upgradable, the SMART6-L eliminates the need for costly hardware replacement as requirements change, while delivering scalable accuracy and performance.

MULTI-CONSTELLATION FOR ENHANCED POSITIONING

Capable of tracking L1, L2 GPS+GLONASS and receiving TerraStar services using L-Band, the SMART6-L improves position availability in obstructed sky conditions. Dual-frequency tracking minimizes the impact of ionospheric disturbances, further enhancing field productivity. Optional TerraStar services improve positioning accuracy outside of L1 SBAS coverage areas.

SMOOTH PASS-TO-PASS ACCURACY USING GLIDE

SMART6-L features NovAtel's GLIDE technology to provide ultra-smooth positioning and exceptional pass-to-pass accuracy. GLIDE's steady, smooth output is especially suited for manual guidance and auto-steer applications and will bridge through short periods of poor satellite availability. Dual-frequency GLIDE further improves the absolute accuracy of the GLIDE position and creates a robust solution, resistant to the effects of high ionospheric activity.

MULTIPLE INTERFACES FOR MAXIMUM FLEXIBILITY

NMEA 0183 compatible RS-232 serial ports and a NMEA 2000 compatible CAN port provide maximum flexibility. The SMART6-L also provides 1 PPS output, an event mark input, simulated radar ground speed output and three daylight readable status LEDs. Built-in magnets simplify mounting although fixed mounting options are also available.

BENEFITS

- + Dual-frequency tracking increases position reliability and mitigates ionospheric effects
- + NovAtel CORRECT™ RTK and PPP provide centimetre-level and decimetre-level positioning accuracy
- + Increased position availability with GLONASS tracking
- + Smooth, consistent positions for pass-to-pass applications with GLIDE technology

FEATURES

- + 120 channels
- + Multi-constellation tracking
- + Simulated radar ground speed output
- + Rugged, integrated design
- + Proven NovAtel Pinwheel antenna technology inside

For more information about our SMART antenna products, visit www.novatel.com/smart-antennas

PERFORMANCE¹

Channel Configuration

120 channels²

Signal Tracking

GPS	L1, L2, L2C
GLONASS	L1, L2
Galileo	E1
BeiDou	B1
SBAS	
L-Band	

Horizontal Position Accuracy (RMS)

Single point L1	1.5 m
Single point L1/L2	1.2 m

NovAtel CORRECT™

» SBAS ³	60 cm
» DGPS	40 cm
» PPP ⁴	(95%) (RMS)
TerraStar-L	50 cm 40 cm
TerraStar-C	5 cm 4 cm
» RTK	1 cm + 1 ppm (RMS) 2.5 cm + 2 ppm (95%)

Maximum Data Rate⁵

Measurements	Up to 50 Hz
Position	Up to 50 Hz

Time to First Fix

Cold start ⁶	<50 s (typical)
Hot start ⁷	<35 s (typical)

Signal Reacquisition

L1	0.5 s (typical)
L2	<1.0 s (typical)

Velocity Accuracy⁸

0.03 m/s RMS

Time Accuracy⁹

20 ns RMS

PHYSICAL AND ELECTRICAL

Dimensions 155 mm diameter
x 81 mm height

Weight <570 g

Connector 14-pin Tyco Ampseal

Mounting

2 x magnetic mount
4 x M4 screw inserts
Optional mounting plate

Power

Input voltage range +8 to +36 VDC
Power consumption¹⁰ 2.9 W (typical)

Status LEDs

Power
Error
Position valid

Power Input and I/O Protection

ISO 7637-2:2004

Emissions and Immunity

ISO 14982: EMC for agricultural machinery

COMMUNICATION PORTS

RS-232 dedicated ports	3
CAN Bus	1
1 PPS	1
Event mark input	1
Ground speed output ¹¹	1

ENVIRONMENTAL

Temperature

Operating	-40°C to +75°C
Storage	-55°C to +90°C

Humidity

MIL-STD-810G Method 507.5

Immersion

MIL-STD-810G Method 512.5

Shock

MIL-STD-810G Method 516.6

Solar Radiation

EN60950-22 8.2

MIL-STD-810G Method 505.5

Salt Fog

MIL-STD-810G Method 509.5

Sand and Dust

MIL-STD-810G Method 510.5

Vibration

Random MIL-STD-810G,
Method 514.6
Sinusoidal ASAE EP455,
5.15.2 Level 1 & 2

Ingress Protection Rating IP67

COMPLIANCE

FCC, IC, CE marking, E-mark

STANDARD FEATURES

- GPS L1 position, velocity and time with SBAS support
- 20 Hz data rates
- Field upgradable software using RS-232 serial ports
- PAC multipath mitigating technology
- Differential correction support for RTCM 2.1, 2.3, 3.0, 3.1, CMR, CMR+ and RTCA
- Navigation output support for NMEA 0183 and detailed NovAtel ASCII and binary logs
- Single-frequency GLIDE smoothing algorithm
- 1 PPS output
- Event mark input
- Ground speed output¹¹

CORRECTION SERVICES

- TerraStar-L
- TerraStar-C
- RTK ASSIST™

FIRMWARE SOLUTIONS

- Dual-frequency GLIDE
- GLONASS tracking
- Galileo tracking
- BeiDou tracking
- L-Band tracking
- ALIGN®
- RAIM
- RTK
- 50 Hz data rates

OPTIONAL ACCESSORIES

- Mounting plate
- Interface cable
- Relay RTK radio module

For the most recent details of this product:

www.novatel.com/products/smart-antennas/smart6-l/

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada) or 403-295-4900

China 0086-21-68882300

Europe 44-1993-848-736

SE Asia and Australia
61-400-883-601

Version 11 Specifications subject to change without notice.

©2016 NovAtel Inc. All rights reserved.

OEM6, NovAtel, ALIGN and Pinwheel are registered trademarks of NovAtel Inc.

RTK ASSIST™, SMART6-L, GLIDE and NovAtel CORRECT are trademarks of NovAtel Inc.

Any use of such marks by NovAtel Inc. is under license. Other trademarks and trade names are those of their respective owners.

D17450 December 2016

Printed in Canada



¹ Typical values (open sky conditions). Performance specifications subject to GNSS system characteristics, Signal-in-Space (SIS) operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.

² Tracks up to 60 L1/L2 satellites.

³ GPS only.

⁴ Requires subscription to TerraStar data service. Subscriptions available from NovAtel.

⁵ 50 Hz while tracking up to 20 satellites. 20 Hz while tracking 20 satellites when used with the Relay RTK Radio.

⁶ Typical value. No almanac or ephemerides and no approximate position or time.

⁷ Typical value. Almanac and recent ephemerides saved and approximate position and time entered.

⁸ Export licensing restricts operation to a maximum of 515 metres per second.

⁹ Time accuracy does not include biases due to RF or antenna delay.

¹⁰ Power consumption values for GPS L1/L2.

¹¹ Only supported on hardware revision 3.03 or greater.